




Standard Container Equipment Specifications

	DRY CONTAINER – SPECIFICATION									
	Type	Container Weight			Interior Measurement				Door Open	
		Gross (KG)	Tare (KG)	Net (KG)	Length (M)	Width (M)	Height (M)	Capacity (M)	Width (M)	Height (M)
20 ft	24,000	2,370	21,630	5.898	2.352	2.394	33.30	2.343	2.280	
49 ft	30,480	4,000	26,480	12.031	2.352	2.394	57.74	2.343	2.280	


Suitable for most type of cargo/General Cargo. Manufactured from either Aluminium or steel. Aluminium containers have a slight larger payload than steel, and steel containers have a slightly larger internal cube.

	REEFER CONTAINER – SPECIFICATION									
	Type	Container Weight			Interior Measurement				Door Open	
		Gross (KG)	Tare (KG)	Net (KG)	Length (M)	Width (M)	Height (M)	Capacity (M)	Width (M)	Height (M)
20 ft	24,000	3,050	20,950	5.449	2.290	2.244	26.70	2.276	2.261	
49 ft	30,480	4,520	25,960	11.690	2.250	2.247	57.10	2.280	2.205	

Recommended for delicate cargo and equipped with a bottom air delivery system ensures refrigerated cargo reaches its destination in optimum condition.


	OPEN TOP CONTAINER – SPECIFICATION									
	Type	Container Weight			Interior Measurement				Door Open	
		Gross (KG)	Tare (KG)	Net (KG)	Length (M)	Width (M)	Height (M)	Capacity (M)	Width (M)	Height (M)
20 ft	24,000	2,580	21,420	5.629	2.212	2.311	32.00	2.330	2.263	
49 ft	30,480	4,290	26,190	11.763	2.212	2.311	65.40	2.330	2.263	

Allowing cargo to be loaded from the top, open top containers are particularly suitable for bulk cargo such as machinery. They are fitted with a PVC tarpaulin cover and attachable bows with cable sealing devices. The container doors can be removed to make the stuffing of cargo more convenient.



HIGH CUBE CONTAINER – SPECIFICATION									
Type	Container Weight			Interior Measurement				Door Open	
	Gross	Tare	Net	Length	Width	Height	Capacity	Width	Height
	(KG)	(KG)	(KG)	(M)	(M)	(M)	(M)	(M)	(M)
40 ft	30,480	3,980	26,500	12.031	2.352	2.698	76.30	2.340	2.585
45 ft	30,480	4,800	25,680	13.544	2.352	2.698	86.00	2.340	2.585

High cube containers gain an extra foot in height compared with general purpose containers. Mostly suitable for light weight cargo or bulk cargo.



FLAT RACK CONTAINER – SPECIFICATION							
Type	Container Weight			Interior Measurement			
	Gross	Tare	Net	Length	Width	Height	Capacity
	(KG)	(KG)	(KG)	(M)	(M)	(M)	(M)
20 ft	30,480	2,900	27,580	5.624	2.236	2.234	27.90
40 ft	34,000	5,870	28,130	11.786	2.236	1.968	51.90

Specially suited for heavy loads or cargo that needs loading from the top or sides, such as pipes and machinery. Flat racks are available with collapsible and non-collapsible containers with or without walls.